Kings®
3D Printing

2700PRO (THREE LASERS)

Kings Industrial SLA 3D Printers

23 Innovative Technologies, High Speed SLA 3D Printing
Efficient and Cost-Effective Prototyping
Bring Your Idea into Reality











LARGE FORMAT SLA 3D PRINTER

Kings

◆ Overview

The Kings SLA 2700Pro sets a new standard in precision 3D printing. Built with a robust marble frame, high-grade ball screw rails, and advanced laser technology, it ensures unparalleled stability and accuracy. Designed for large-scale printing, it features silent motion, laser liquid level detection, and remote monitoring capabilities, ideal for diverse industrial applications with optimized resin materials.

◆ Advantage

- **Enhanced Printing Efficiency**
  - → Intelligent high speed scanning system, 15m/s
  - → Variable laser spot and variable power
  - → Automatic identifying upskin and downskin with differentiated parameters
  - → Different Parameter databases with different layer thickness
- **Long-term Printing Stability**
  - → Key components from international top brands
  - → Full marble structure for enhanced recoating and scanning stability
  - → High stiffness light recoater to ensure recoating accuracy and efficiency
  - → Compensation algorithm for multi-head system, ensuring uniform curing in the printing range

◆ Ideal Applications

Shoe Mold Manufacturing | Prototyping | Architecture | Sculpture | Medical

Dental | Military | Automotive | Animation | Electronics

Web: www.kings3dprinter.com | Email: market@kings3dprinter.com

Follow us on @kings3dprinter @kings_3dprinter

LARGE FORMAT SLA 3D PRINTER

Kings

◆ Technical Data

Max Printing Size	2700*900*800mm
Machine Size	351cm(W)*196cm(D)*273cm(H)
Rated Power Consumption	3.0KVA
Machine Weight	3750kg
First Tank Resin	2650kg
Beam Size (diameter @1/e²)	0.08-0.8mm(Variable beam sizes)
Max Scanning Speed	15.0m/s
Layer Thickness	0.05mm~0.2mm
Accuracy	±0.15(L≦100mm)； ±0.15%*L(L>100mm)
Laser Type	Solid-state frequency tripled Nd: YV04
Wavelength	355nm
Power	Resin surface power≥300 mw
Variable Beam System	Galvo/Closed-loop
Main Structure	Marble recoater frame, marble elevator holder and marble scanning system base
Coating Mode	lntelligent position vacuum recoating
Vertical Resolution Ratio	0.0005mm
Repeat Positioning Accuracy	±0.01mm
Motion Control System	Closed-loop
Machine Control Software	KINGS 3D control software
lnput Data File Format	STL/SLC
Operating System	Windows 10
Network Type and Protocol	Ethernet，TCP/IP
Electrical Requirement	200-240VAC 50/60Hz,single-phase,10A
Ambient Temperature	20-26°C(72-79F)
Relative Humidity	<40%，non-condensing

Shenzhen Kings 3D Co., Ltd
Building B, No. 148 Huanli Road, Yungu Community, Xinhu Street, Guangming District, Shenzhen, China.
No.178, Dingxing Road, High-tech Zone, Zhuhai City, Guangdong Province
Web: www.kings3dprinter.com
Mob/Whatsapp: +86 17727416895
Email: market@kings3dprinter.com